

RIVER Series ZNC Drilling
New Generator and Controller Design

**Normal screen
(Standard)**



**Touch screen
(Optional)**



**Touch screen
(Optional)**



RIVER Series

Features:

1. The sparking drilling is use of digital control mechanism, which can effectively enhance the small size drilling and speed by stability.
2. With HP1 high-speed circuit to enhance drilling speed.

Specification:

Model no	River 35	River 45
Table travel (X,Y axes)	350 x 250 mm	450 x 350 mm
Work table size	600 x 300 mm	600 x 376 mm
Z axis travel	350 mm	350 mm
W axis travel	200 mm	200 mm
Max. workpiece height	330 mm	360 mm
Max. workpiece weight	250 kgs	600 kgs
Power input	According to local voltage	According to local voltage
Max. average current	32 Amps (64A optional)	32 Amps (64A optional)
Power capacity	3.8 KVA	3.8 KVA
Electrode diameter	0.1 ~ 3.0mm (3.0 ~ 6.3mm Opt.)	0.1 ~ 3.0mm (3.0 ~ 6.3mm Opt.)
Machine net weight	1000 kgs	1300 kgs
Depth / Width / Height	1200 x 1550 x 2230 mm	1520 x 1620 x 2230 mm

★Due to continuous research and development, all specifications and design characteristics are subject to change without prior notice.



No.1-1, Zhong Zheng Rd., Wu-Feng Dist., Taichung City, Taiwan 41361, R.O.C.

Tel:+886-4-23394805 Fax:+886-4-23332038

www.octece.com E-mail: sales@octec.com.tw / sunnyliao@octec.com.tw

